Nakamura NT-Flex

Lathe · CNC lathe



Article number	**NP-N00008**
Condition	**New machine**
Control	**Fanuc 0i-TF Plus**
Turning diam.	**150 mm**
Turning length	**405 mm**

Axes:

Turning length	max. 405 mm
Turning diameter	max. 150 mm
Bar capacity	32 / 38 mm
Distance between spindles	200–655 mm

Basic equipment:

Power	5.5 / 7.5 kW
Speed	8,000 / 10,000 rpm
Tool holder	BMT 35

Gegenspindel:

Power	5.5 / 7.5 kW
Speed	8,000 / 10,000 rpm
Tool holder	BMT 35

Tel. +49 (0) 8142 / 44 87 - 100
Fax +49 (0) 8142 / 44 87 - 155
info@gs-wzm.de
www.gs-werkzeugmaschinen.de

Gläsener + Schmidt GmbH
Gewerbering 6
82140 Olching
Deutschland

Subject to prior sale and technical errors.

Achsen:

Number of axes	8 (+2)
Movement X1	110.5 (150.5) mm
Movement X2	110.5 mm
Movement X3	110 mm
Movement Z1	455 mm
Movement Z2	455 mm
Movement Y1	+/- 25 mm
Movement Y2	+/- 25 mm
Movement B2	455 mm
Rapid traverse X	24 m/min
Rapid traverse Z	32 m/min
Rapid traverse Y1	20 m/min
Rapid traverse Y2	6 m/min
Rapid traverse B2	32 m/min

Grundausstattung:

- C-axis (MS+CS)
- Provision for coolant flushing via MS
- Provision for coolant flushing via CS
- Upper tool turret, 12 stations, Driven tool h.
- Lower tool turret, 12 stations, Driven tool h.
- IRCO bar feeder interface
- Provision for oil mist extraction
- MK1 coolant interface
- 8 free M-commands per turret
- Storage area on the control panel

Tel. +49 (0) 8142 / 44 87 - 100
Fax +49 (0) 8142 / 44 87 - 155
info@gs-wzm.de
www.gs-werkzeugmaschinen.de

Gläsener + Schmidt GmbH
Gewerbering 6
82140 Olching
Deutschland

Subject to prior sale and technical errors.