Takumi H 10

Milling machine · 3-axis machining centre



Article number	**NP-TaH0002**
Condition	**New machine**
Control	**Heidenhain TNC 640 / TNC7**
Speed	**15000 rpm**
Movement X/Y/Z	**1020/700/500 mm**
Tool holder	**SK 40**

Working area:

Movement X	1,020 mm
Movement Y	700 mm
Movement Z	500 mm
Clamping surface	1,050 x 700 mm
Table load	max. 800 kg

Spindle (Standard):

Power	max. 14 kW
Torque	max. 89.4 Nm
Speed	max. 15,000 rpm
Tool holder	SK 40
Tool changer	30 positions

Spidle option 1:

Power	max. 14 kW
Torque	max. 89.4 Nm
Speed	max. 15,000 rpm
Tool holder	BBT40 / HSK63-A

Tel. +49 (0) 8142 / 44 87 - 100
Fax +49 (0) 8142 / 44 87 - 155
info@gs-wzm.de
www.gs-werkzeugmaschinen.de

Gläsener + Schmidt GmbH
Gewerbering 6
82140 Olching
Deutschland

Subject to prior sale and technical errors.

Spindle option 2:

Power	max. 34 kW
Torque	max. 139.6 Nm
Speed	max. 15,000 rpm
Tool holder	SK40 / BBT40 / HSK63-A

Spindle option 3:

Power	max. 35 kW
Torque	max. 116.5 Nm
Speed	max. 20,000 rpm
Tool holder	HSK63-A

Spindle option 4:

Power	max. 45 kW
Torque	max. 43.5 Nm
Speed	max. 24,000 rpm
Tool holder	HSK63-A

Spindle option 5:

Leistung	max. 26 kW
Drehmoment	max. 13,5 Nm
Drehzahl	max. 36.000 U/min
Werkzeugaufnahme	HSK50-E

Measurements:

Measurements (LxWxH)	4,520 x 4,290 x 2,830 mm
Weight	approx. 9,100 kg

Tel. +49 (0) 8142 / 44 87 - 100
Fax +49 (0) 8142 / 44 87 - 155
info@gs-wzm.de
www.gs-werkzeugmaschinen.de

Gläsener + Schmidt GmbH
Gewerbering 6
82140 Olching
Deutschland

Subject to prior sale and technical errors.